



MAXHUB XCore Room Kit for Microsoft Teams Rooms

Model: XT10-WS Kit


MAXHUB XT10-WS Kit incorporates a high-quality Speakerphone and USB Camera. With the inclusion of a mobile Speakerphone and camera, this bundle adeptly caters to participants' dynamic audio and video needs, driving a flexible and seamless collaboration experience. Compatible with Microsoft Teams Rooms, the Kit also helps to facilitate the switch to Microsoft Teams Rooms smart spaces for BYOD scenarios, enhancing Teams-native audio and video experiences while accommodating cost-balance needs.




One Cable Technology



Device Management



Flexible & Ease of Installation



Easy Content Sharing



3-Year Warranty & Local support



Secured and Managed

Product Specification

Type	Mini-PC
CPU	Intel i3-1220P TDP: 28W
Memory	8GB DDR4 3200MHz
Optional hard disk	128GB SATA SSD (M.2-2280 SATA3 up to 6Gb/s)
Graphics	Intel® UHD Graphics for 12th Gen Intel® Processors;
Chipset	ADL PCH-P
Sound Card	USB Audio, HS-100B, Cmedia
Network	1000Mbps RJ45
Operating system	Windows 11 IoT Enterprise SAC

Certifications

Certifications	Microsoft Teams Rooms
----------------	-----------------------

I/O Port

USB-A 3.0	4
LAN	1
USB-C (For Teams Rooms Console)	1
HDMI OUT	1
Audio OUT	1
AC POWER	1
Kensington lock slot	1

Power

Power Supply Mode	AC POWER
Power Requirements	100-240V AC 50/60Hz
Max Power	90W

Accessories (included in the package)

Wall Bracket	×1
PC Bracket	×1
Cable Cover Screw	×2
Machine Screw	×4
Expansion Screw	×4
Self-tapping Screw	×4
Cable Cover	×1
HDMI Cable (1.8m/5.9ft)	×1
Power Cord (1.8m/5.9ft)	×1
Quick Start Guide	×1

Physical Specifications

Dimension L × W × H	230mm × 185mm × 41.5mm / 9.06" × 7.28" × 1.63"
Dimension (package) L × W × H	342 × 246 × 146mm / 13.46" × 9.69" × 5.75"
Net Weigh	1.36kg / 3lbs
Gross Weight	4.36kg / 9.6lbs

Environmental Conditions

Operation Temperature	0°C-40°C / 0°F-104°F
Operation Humidity	10%-90%RH
Storage Temperature	-20°C-60°C / -4°F-140°F
Storage Humidity	10%-90%RH
Altitude	Below 5000m / 196850"

Display

Size	10.1 inch
Resolution	1920 (H) x 1200 (V)
Frequency Refresh Rate	60Hz
NTSC	Min.62%, Typ.65%
Back Light Unit	ELED
Brightness with glass	Min.250cd/m ² , Typ.300cd/m ²
Life Time	≥ 20000 Hours

Touch System

Type	Capacitive touch
Touch Tool	Finger
Accuracy	± 2mm / 0.08"
Touch Point	10 points touch
Minimum object size	6mm / 0.24"

I/O Port

HDMI INGEST (SCREEN SHARE)	1
USB-A (USB PERIPHERAL)	1
USB-C (TO PC)	1
3.5mm (AUDIO OUT)	1

Physical Specifications

Dimension L×H×D	245 × 164.3 × 77.4mm / 9.65" x 6.47" x 3.05"
Dimension (package) L×W×H	332 × 246 × 166mm / 13.07" x 9.69" x 6.54"
Net Weight	880g / 1.94lbs
Gross Weight	2.38kg / 5.25lbs

Accessories (included in the package)

USB Type-C Cable (Type C-C) 5m / 16.4ft	×1
HDMI Cable 1.8m / 5.9ft	×1
Quick Start Guide	×1

Power

Power Requirements	15V 3A (Type-C PD)
Overall Power (Max.)	20W
Standby Power	≤ 0.5W

Environmental Conditions

Operation Temperature	0°C-40°C / 0°F-104°F
Operation Humidity	10%~90%RH
Storage Temperature	-20°C-60°C / -4°F-140°F
Storage Humidity	10%~90%RH
Altitude	Below 5000m/ 196850"

Connect	USB-A Dongle for wireless connection to PC PC via combined USB-A (to PC) and USB-C (to BM35) cable; smartphone via Bluetooth
----------------	---

Compatible	Compatible with Windows 7/8/8.1/10/11, MAC OS 10.10 and above
-------------------	---

User Interface Features

Physical button user controls for	Touch button user controls for	LED Indicator light
Power on/off	Call/hang up	Annular LED
Bluetooth Pairing	Mute	
	Volume +/-	

Wireless	
Bluetooth	
Version	BT5.3
Operating Frequency	2.4GHz
Operating Distance	10m/393.7"
Compatibility	Support audio playback, HD audio input
Dual Bluetooth Design	One dedicated Bluetooth for connection to the MAXHUB Bluetooth Dongle, the other Bluetooth can be flexibly connected to smartphones and other devices.
Wireless connection to your computer via the included Bluetooth Dongle; Expand your BM35 by wireless daisy-chain to suit meeting rooms with up to two BM35.	
NFC	Connect your Android device with NFC

Battery	
Battery Type	Lithium-ion battery
Battery Capacity	4400mAh
Talk Time	up to 15h
Music Time	up to 8h
Charge Time	4h 40m (5V 1A)

Physical Specification	
Dimensions(LxWxH)	126.7 x 126.7 x 35.3 mm (5.0 x 5.0 x 1.4 inch)
Dimension(package)(LxWxH)	1pcs 225 x 158 x 50 mm (10.0 x 6.2 x 2.0 inch) 20pcs 472 x 335 x 292 mm (18.6 x 13.2 x 11.5 inch)
Net Weight	0.47Kg/1.04lbs
Gross Weight	1pcs 0.71kg/1.57lbs 20pcs 16.89kg/37.24lbs

Audio Features	
Microphone	
Quantity	8
Voice Pickup Range	6m/236.2"
Type	Digital Microphone
Microphone Frequency Range	(1) USB: 100Hz ~ 12kHz; (2) Bluetooth: 100Hz ~ 7.5kHz
Special Features	AI noise reduction, filter-off background noise such as keyboard noise, table and chair moving noise, road noise, etc.
Speaker	
Sound Channel	1.1
Output Power	5W + 3W
Maximum Sound Pressure	80dB SPL@1m
Distortion	<7% (80Hz ~ 350Hz); <3% (351Hz ~ 4kHz); (4.1kHz~5.8kHz)
Signal to Noise Ratio	>75dB
Frequency Range	80Hz ~ 18kHz
Special Features	Using treble + bass combo design for wider music bandwidth.

Environmental	
Operation Temperature	0°C-40°C
Operation Humidity	10% ~ 90% RH
Storage Temperature	-20°C-60°C
Storage Humidity	10% ~ 90% RH
Altitude	Below 5000 meter/196850"

Supported Applications	MAXHUB Align software for Windows & Mac
-------------------------------	---

Platform Certification	ZOOM Certified Supports major VC software including ZOOM, Microsoft® Teams, Google Meet, Google Hangouts, Cisco WebEx®, RingCentral, etc.
-------------------------------	--

Warranty	3-year hot swap warranty
-----------------	--------------------------

What's in the box	1 x USB TYPE-C Cable (1.0m/39.37 inch) , 1 x USB dongle
--------------------------	---

Camera Parameters

Image Sensor	IMX577
Pixel	12MP
Output Resolution	H.264/MJ: (1) 3840×2160 (2) 2560×1440 (3) 1920×1080 (4) 1280×720 (5) 1024× 576 (6) 960×540 (7) 800× 600 (8) 640×480 (9) 640×360 (10) 480×270 (11) 352×288 (12) 320×240 (13) 320×180 NV12 / YUY2: (1) 1920×1080 (2) 1280×720 (3) 640×360

Focus Method	FF
Field Of View	FOV(H): 109.1° FOV(V): 74.4° FOV(D): 117.8°
Touch Point	2.4
Digital Noise Reduction	Yes
Output Format	MJPEG;H.264;YUY2;NV12
White Balance	Yes
Exposure	Yes

I/O Port

USB Type-C(Device)	1
--------------------	---

Microphone Parameters

Quantity	2
Pickup Distance	4m/157.5"

Physical Specifications

Dimension L×H×D	85×63×68.2mm/3.35"×2.48"×2.69"
Dimension (package) L×W×H	160×144×114mm/6.3"×5.67"×4.49"
Net Weight	175g/0.39lbs
Gross Weight	300g/0.66lbs

Accessories

USB Cable	×1
Privacy cover	×1
Hand-tightened screw	×1

Environmental Conditions

Operation Temperature	0 C~40 C
Operation Humidity	10%~90%RH
Storage Temperature	-20 C~60 C
Storage Humidity	10%~90%
Altitude	Below 5000m/196850"


Package Includes

- XC13T Mini-PC x1
- TCP20T Touch Control Panel x1
- UC BM35 x1
- UC M31 x1

Package Physical Specifications

- Dimension (package) L×W×H 890x270x265mm/35.04"x10.63"x10.43"
- Net Weight 8.034kg/17.7lbs
- Gross Weight 9.91kg/21.85lbs

Connection



Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.