

Product information

C5 Racks – The sideboard solution with integrated ventilation concept

Revolutionary for the device installation in sideboards

- 1, 2, or 3 bay models available
- Includes front and rear 14 space rail
- Thermal management is provided by two thermostatically controlled 59 CFM fans per bay
- Fresh air is aspirated in at the base, the exhaust to the front is almost invisible beneath the cover plate of the cabinet
- Thermostatically controlled fans turn on when inside Credenza temperature reaches 30° C, and turn off at 29° C
- The noise level is around 32 dBA. The ventilation system as a whole is encapsulated by the furniture, thus virtually inaudible.
- Finishing kits in different styles are available as well as a complete kit to facilitate the creation of custom millwork. This kit includes all required drawings in electronic format, and all of the required mounting and assembly hardware.



Cat.No.	Model	Width mm (without finishing)	useable depth mm	useable height RU
IC5F1	1 bay	531	525	14
IC5F2	2 bay	1093	525	14
IC5F3	3 bay	1656	525	14



CFR Series – simply a lot of space in a small place

Maximizes the amount of useable rackspace

- A strong welded frame allows for pre-loading equipment and transportation to the installation site
- Low profile design maximizes amount of useable rackspace
- Available in 41 and 46 cm useable depth from 8 to 14 RU
- Comes standard with two adjustable front to rear lacing bars for cable dressing or mounting accessories
- Rackrail features offset cable tie area which keeps the rack to a slim 49 cm width
- Optional runner kits allow the rack to easily slide in or out of cabinets and credenzas



Cat.No. 16" 406 mm Depth	Cat.No. 18" 457 mm Depth	Overall Height mm	useable Height mm	useable Height RU
CFR-8-16	CFR-8-18	379	356	8
CFR-9-16	CFR-9-18	424	400	9
CFR-10-16	CFR-10-18	468	445	10
CFR-11-16	CFR-11-18	513	489	11
CFR-12-16	CFR-12-18	557	533	12
CFR-13-16	CFR-13-18	602	578	13
CFR-14-16	CFR-14-18	646	622	14



SRSR Serie – pulls out and rotates to provide convenient rear access

The best convenient solution for smaller installations

- Service friendly rack system for millwork and cabinets
- Unique: Pulls out and rotates for equipment servicing
- Removable rack frame allows in-shop integration and on-site installation of equipment, saving time in the field
- Shortens installation & service time:
 - Rear access to equipment connections
 - Locks in place at 0°, 60°, and 90° positions for easy installation and servicing
- Integral cable management system provided
- Available in 19" and 23" useable depths (480 / 580 mm)
- Sizes range from 12 – 30 RU
- Up to 110 kg weight capacity



Cat. No.	Description	pulls out	weight capacity
SRSR-2-xx	„xx“ for useable spaces (12 – 24 RU)	480 mm	2 slide 55 kg
SRSR-4-xx	„xx“ for useable spaces (12 – 30 RU)	480 mm	4 slide 110 kg
SRSR-X-xx	„xx“ for useable spaces (12 – 30 RU)	580 mm	4 slide 90 kg



SRS Serie – Sliding Rail System simplifies equipment installation in cabinet

- Pulls out 480 mm for equipment servicing
- Provides rear access to equipment
- Optional cable carriers provide effective cable management
- Available from 8 to 20 RU
- Available with 2 slides (57 kg capacity) and 4 slides (113 kg)



Cat. No.	Note	pulls out	weight capacity
SRS2-xx	„xx“ for usable spaces (8 – 20 RU)	480 mm	2 slide 57 kg
SRS4-xx	„xx“ for usable spaces (8 – 20 RU)	480 mm	4 slide 113 kg



Large systems installed easily and compactly

AXS System for Millwork and In-Wall

- Slide-out rack frame saves time & reduces labor
- Entire bays of equipment can be rolled out for service and installation flexibility
- Service tracks include built-in level to reduce installation and servicing time
- Telescoping service stand elevates service tracks from 90 – 1.015 mm
- Unrestricted rear access to equipment & cabling
- Cable management tray provides additional capacity for large cable bundles
- Available in 16", 20" or 26" depths (410, 510 and 660 mm)
- Available from 15 – 43 RU
- Up to 300 kg weight capacity with proper distribution



Cat. No.	Note	Extension Length	Frame Depth
AXS-xx-26	„xx“ for useable spaces (15 – 43 RU)	1.220 mm	660 mm
AXS	plus useable spaces (15 – 43 RU)	1.220 mm	510 mm
AX-SX	plus useable spaces (10 – 43 RU)	635 mm	510 mm
SAX	plus useable spaces (15 – 43 RU)	1.220 mm	410 mm
SSAX	plus useable spaces (10 – 43 RU)	635 mm	410 mm

AX-SXR Series – Rotating AXS System for Millwork and In-Wall

- Like the AXS Series, but in addition:
- Slide-out rack frame rotates for equipment servicing
- Simplifies installation of larger electronics systems in cabinet
- Detachable rack frame allows for off-site equipment integration
- Up to 205 kg weight capacity with proper weight distribution
- Integral cable management system provided

Cat. No.	Note	Extension Length	Frame Depth
AX-SXR-xx	„xx“ for useable spaces (15 – 43 RU)	790 mm	510 mm

